



(12) **United States Patent**
Koganehira et al.

(10) **Patent No.:** **US 9,409,408 B2**
(45) **Date of Patent:** **Aug. 9, 2016**

(54) **LIQUID EJECTING APPARATUS**

(71) Applicant: **SEIKO EPSON CORPORATION**,
Tokyo (JP)

(72) Inventors: **Shuichi Koganehira**, Matsumoto (JP);
Yasuhiko Kosugi, Matsumoto (JP);
Takeshi Iwamuro, Matsumoto (JP);
Tomohiko Sano, Shiojiri (JP); **Kenji**
Matsumoto, Chino (JP); **Ryohei Ito**,
Shiojiri (JP)

(73) Assignee: **Seiko Epson Corporation**, Tokyo (JP)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/424,008**

(22) PCT Filed: **Aug. 28, 2013**

(86) PCT No.: **PCT/JP2013/005085**
§ 371 (c)(1),
(2) Date: **Feb. 25, 2015**

(87) PCT Pub. No.: **WO2014/034110**
PCT Pub. Date: **Mar. 6, 2014**

(65) **Prior Publication Data**
US 2015/0224783 A1 Aug. 13, 2015

(30) **Foreign Application Priority Data**
Aug. 31, 2012 (JP) 2012-192402

(51) **Int. Cl.**
B41J 29/393 (2006.01)
B41J 2/175 (2006.01)

(52) **U.S. Cl.**
CPC **B41J 2/17566** (2013.01); **B41J 2/17509**
(2013.01); **B41J 2/17546** (2013.01)

(58) **Field of Classification Search**

CPC B41J 29/393; B41J 29/38; B41J 29/02;
B41J 11/42; B41J 2/04505; B41J 13/02;
B41J 2/0451; B41J 11/0095; B41J
2002/17569; B41J 2/14153; B41J 2/195
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

7,600,835 B2 10/2009 Moriyama et al.
7,850,263 B2 12/2010 Shinada et al.

FOREIGN PATENT DOCUMENTS

JP 2005-041025 2/2005
JP 2005-053110 3/2005
JP 2007-320096 12/2007
JP 2008-254395 10/2008
JP 2012-111167 6/2012

OTHER PUBLICATIONS

PCT/JP2013/005085, International Search Report dated Mar. 12,
2013. (2 pages).

Primary Examiner — Lamson D Nguyen

(74) *Attorney, Agent, or Firm* — Workman Nydegger

(57) **ABSTRACT**

An object is to improve a user's convenience. There is provided a liquid ejecting apparatus including a head ejecting a liquid onto a medium; a containing unit containing the liquid; and a mounting unit on which a storage material storing a liquid amount of the containing unit is mounted. If the storage material is removed from the mounting unit when the liquid ejecting apparatus performs an operation, the liquid ejecting apparatus selects any one state between a first state of stopping the operation and a second state without stopping the operation.

6 Claims, 8 Drawing Sheets

ITEM CONSUMPTION COUNTER C(%)	1. DISPLAY ON DISPLAY PANEL	2. WRITE ON CHIP UNIT	3. PRINTING OPERATION	4. PRINTING OPERATION WHEN CHIP UNIT IS REMOVED
A. $C < 100$	PRINTABLE	YES	CONTINUE	STOP
B. $100 \leq C < 106$ (100+a)	REPLACEMENT TIME	NO	CONTINUE	CONTINUE
C. $106 \leq C < 112$ (100+2a)	WARNING OF STOPPAGE OF PRINTING	NO	CONTINUE	CONTINUE
D. $112 \leq C$	REPLACEMENT TIME EXCEEDED	NO	STOP	(STOPPED) (ALREADY)